Appl. No.: 10/623,091

Reply to Office Action of: June 29, 2004

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions, and listing, of claims in the present application:

Listing of Claims:

- 1. (canceled)
- 2. (currently amended) A card connector assembly as defined in claim 1, further comprising:

a card receiving slot:

an extraction prevention mechanism for preventing extraction of a card inserted in the card receiving slot; the extraction prevention mechanism having a frictional retention member provided within the card receiving slot, held so as to be movable in a direction essentially perpendicular to the main surface of the card inserted therein; a cam mechanism for urging the frictional retention member toward the main surface of the card; and an operating member for driving the cam mechanism; wherein extraction of the card is prevented by operating the operating member to press the frictional retention member against the main surface of the card;

- a main body; and
- a cam protrusion provided on a bottom wall of the main body.
- 3. (currently amended) A card connector assembly, comprising: as defined in elaim 2

a card receiving slot;

an extraction prevention mechanism for preventing extraction of a card inserted in

the card receiving slot; the extraction prevention mechanism having a frictional retention

member provided within the card receiving slot, held so as to be movable in a direction

9.17.04/1296530 1.DOC

-2-

No.0554 P. 4/7

Appl. No.: 10/623,091

Reply to Office Action of: June 29, 2004

essentially perpendicular to the main surface of the card inserted therein; a cam mechanism for urging the frictional retention member toward the main surface of the card; and an operating member for driving the cam mechanism; wherein extraction of the card is prevented by operating the operating member to press the frictional retention member against the main surface of the card;

a main body; and

a cam protrusion provided on a bottom wall of the main body;

wherein the cam mechanism has:

a first plate on which the frictional retention member is mounted, provided above the bottom wall; and

a second plate provided underneath the first plate, slidably movable by the operating member to a position corresponding to the cam protrusion; wherein

the first plate having the frictional retention member mounted thereon is caused to be urged toward the card by the second plate riding up on the cam protrusion by operation of the operating member.

- 4. (currently amended) A card connector assembly as defined in elaim 1 claim 2, wherein:
 - the frictional retention member is formed from rubber.
 - (original) A card connector assembly as defined in claim 2, wherein:
 the frictional retention member is formed from rubber.
 - (original) A card connector assembly as defined in claim 3, wherein:
 the frictional retention member is formed from rubber.

Appl. No.: 10/623,091

Seg. 18. 2003 1:04PM

Reply to Office Action of: June 29, 2004

7. (currently amended) A card connector assembly as defined in <u>claim 1 claim 2</u> wherein:

the operating member comprises a slider operably connected to the cam mechanism.

- (original) A card connector assembly as defined in claim 3, wherein:
 the operating member comprises a slider operably connected to the first plate.
- 9. (currently amended) A card connector assembly as defined in elaim 1 claim 2, further comprising:

at least two cam protrusions provided on a bottom wall of the main body, a first one of the cam protrusions being configured to retain the cam mechanism without urging the frictional retention member into contact with the main surface of the card, and a second one of the cam protrusions being configured to urge the frictional retention member into contact with the main surface of the card.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
☐ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.